

Concrete Grinding Lube (CGL)

Lubricant for Diamond Tools when Grinding, Cutting or Drilling

Description

CGL is an innovative lubricant specifically formulated for use with diamond tooling. **CGL** has proven extremely effective to significantly increase cutting speeds and substantially reduce tool wear.

Uses

CGL is suitable in all diamond cutting applications, including:

- Concrete Grinding
- Concrete Cutting
- Concrete Coring
- Marble & Granite Grinding
- Marble & Granite Cutting
- Marble & Granite Polishing
- Road & Runway Grooving
- Brick & Tile Cutting

Advantages

Greater Cutting Speed

Greater cutting speed means more output per labour hour resulting in work being completed in less time. Tool costs are significantly decreased as tools maintain their cutting edges up to 35% longer.

The benefits of **CGL** increase the effectiveness of your business translating to greater profits.

Environmentally Friendly

CGL is environmentally friendly and meets Australian Standard 4351 as a readily biodegradable material.

CGL directly increases efficiency leading to further environmental benefits including reduced water and power consumption.

Mix Ratio

- 1 litre of **CGL** will dilute into 25 litres of water (1:25)
- **CGL** can be used neat (undiluted) if required.

Limitations

Always read MSDS before use of any product.

Storage Period: 2 years (5-35°C)

Packaging: 5, 15 and 200 litre plastic containers

First Aid

For safety information or Material Safety Data Sheet call EIC Customer Service on 08 8121 7867.

For emergency please contact 24 hour mobile 0413 075 994.