

TIMBER FLOORS CARE INSTRUCTIONS

Once your timber floor has been polished, sealed or coated with Ecoshield products, it is important that the following measures are taken to prolong the life of your floor and maintain a high performance finish.

CLEANING AND MAINTENANCE

Clean up any broken glass and wipe up food and beverage spillages immediately.

Ensure you lift and not drag, equipment, tables, chairs and any other utility items.

Sweep floors regularly to remove surface debris using a fringe mop. We advise not to use vacuum cleaners as the brushes on the vacuum head can wear thin, exposing metal which can then lead to a scratched surface.

Damp mop floor with Eco Clean – 100ml in 5 litres of cold or luke warm water only.

Remove black heel marks and other stubborn marks by using undiluted Eco Clean with a Chux wipe or similar soft cloth.

WEEKLY

- Perform the procedure above.
- Inspect floor for wearing of the surface.
- Inspect for damage that may require repair or special treatment.

MONTHLY

- Perform the procedure above.
- Apply Eco Polish and buff into the floor to leave a glossy protective clear coat.

PRECAUTIONS

After your floor has been sealed it is recommended there is no foot traffic for 24 hours, 72 hours is optimal though.

Light foot traffic may be possible after 4-6 hours in drying conditions of 25°C and 50% relative humidity.

It is advised that no shoes should be worn on the floor for the first 4-6 hours after drying.

Avoid dragging of furniture over the coated surface at all times.

Place mats at entrances on the inside as well as outside where possible as this will reduce the abrasive particles from exterior areas being brought onto the floor.

It is recommended that mats be placed on the floor 2 days after the coating is applied.

Ensure protective pads are on all furnishing floor contact points.