

PRODUCT DATA SHEET

CHAINLINK

2-PACK ADDITIVE FOR USE IN ECO SEAL

PRODUCT DESCRIPTION

Chainlink is a specially formulated additive designed for use in Eco Seal. This advanced 2-pack system enhances the strength and abrasion resistance of the coating, ensuring superior performance and durability. By incorporating Chainlink, the protective properties of Eco Seal are significantly improved, extending the lifespan of coated surfaces in high-wear environments—making it highly recommended for surfaces exposed to vehicular traffic and hot tyres.

This formulation is ideal for applications where durability and enhanced surface protection are critical. Chainlink's formulation has been tested to provide optimal adhesion and compatibility with Eco Seal, ensuring seamless integration and ease of application. This results in a uniform coating with reinforced mechanical properties, reducing the risk of premature wear and surface damage.

KEY BENEFITS

- **Enhanced Durability:** Provides superior resistance to abrasion, significantly improving wear protection and extending the lifespan of the coating for long-lasting performance.
 - **Superior Adhesion:** Ensures a strong and lasting bond, allowing for seamless integration with Eco Seal, enhancing durability and coating performance.
 - **Increased Strength:** Enhances and reinforces the mechanical properties of the coating, ensuring greater resistance to physical stress and maintaining structural integrity over time.
 - **Consistent Performance:** Ensures a uniform and reliable finish with enhanced protective properties, maintaining coating integrity and long-term effectiveness in various conditions.
 - **Minimised Maintenance:** Significantly decreases the frequency of required reapplications, ensuring long-lasting protection while reducing time and effort spent on upkeep.
-

APPLICATION

- Shake bottle well before use.
- **Mixing Proportions:**
 - Mix 125ml of Chainlink Additive into 5 litres of Eco Seal
 - Mix 375ml of Chainlink Additive into 15 litres of Eco Seal
- Stir thoroughly to achieve a smooth and even mixture.
- Allow adequate curing time as per the Eco Seal manufacturer's recommendations to ensure maximum performance.

- Proper mixing and application are essential to achieving the intended durability benefits. Failure to follow the recommended proportions or application techniques may result in suboptimal performance.

LIMITATIONS

- Always refer to the Safety Data Sheet (SDS) before product application.
- Chainlink is specifically designed for use with Eco Seal and should not be mixed with other coatings or additives, as this may compromise performance.
- Store in a dry, well-ventilated area and avoid direct exposure to extreme temperatures.
- Ensure proper surface preparation before application to maximise adhesion and effectiveness.

TECHNICAL SPECIFICATIONS – GRIPPY STUFF STEP ONE

Property	Specification
Appearance	Milky white liquid
Odour	Slight
Specific Gravity	1.07
Flammability	Non-flammable
Water Solubility	Completely dispersible
Shelf Life	2 years (store at 5-35 °C)
Packaging Sizes	Available in 1, 5, 15 and 200 litre containers

HEALTH & SAFETY

For detailed safety information, refer to the **latest Safety Data Sheet (SDS)** available at www.ecoshield.com.au.

For emergencies, contact 24-hour mobile support at 0413 075 994.

First Aid Measures

- **If swallowed:** Do not induce vomiting. Dilute with milk or water and seek medical advice if necessary.
- **If in eyes:** Rinse immediately with water for several minutes. Remove contact lenses if present. Continue rinsing and seek medical attention if irritation persists.
- **If on skin:** Wash thoroughly with soap and water. If irritation persists, seek medical assistance.

Poisons Information Centre: 131 126.


MANUFACTURER'S DISCLAIMER


The use of this product in combination with other manufacturers' products may impact its performance. Ecoshield Performance Coatings Pty Ltd is not responsible for any issues arising from improper application or deviation from recommended procedures.


Product formulations and application methods are subject to updates—please ensure you have the latest information.

CONTACT INFORMATION

Ecoshield Performance Coatings Pty Ltd

 08 8185 7148

 info@ecoshield.com.au

 www.ecoshield.com.au

 Date of Revision: May 2026