

COATED & POLISHED CONCRETE CARE INSTRUCTIONS

To uphold the durability and high-performance finish of your concrete floor, it's essential to follow these measures after polishing, sealing or coating with Ecoshield products. This will ensure your investment remains protected and visually appealing for years to come.

CLEANING AND MAINTENANCE

Immediate Care

- Immediately clean up any broken glass and wipe up food and beverage spills.
- Lift and carry, rather than drag, equipment, tables, chairs, and other items to prevent scratches.

Daily Maintenance

- **Sweep regularly:** Use a fringe mop to remove surface debris. Avoid using vacuum cleaners, as the metal on the vacuum head's brushes can become exposed and scratch the floor.
- **Damp mop:** For a deeper clean, damp mop the floor using a solution of Eco Clean.
- **Spot clean:** For black heel marks and other stubborn spots, use undiluted Eco Clean with a soft cloth like a Chux wipe.

Weekly and Monthly Maintenance

- **Weekly:** Perform the daily maintenance tasks. Inspect the floor for any signs of wear or damage that may require special attention.
- **Monthly:** Repeat the weekly maintenance. Apply and buff in Eco Polish to add a glossy, protective clear coat.

PRECAUTIONS

Foot Traffic and Furniture

- **Initial Curing:** For optimal results, we recommend keeping all foot traffic off the floor for 24 hours after the final seal has been applied. An ideal curing period is 72 hours.
- **Light Use:** In optimal drying conditions of 25°C and 50% relative humidity, light foot traffic may be possible after 4-6 hours. However, to avoid any potential scuffing, it is best to wear socks and avoid shoes during this initial period.
- **Furniture Placement:** To prevent scratches and damage to the coated surface, avoid dragging any furniture or other items over the floor at all times. Use furniture pads to protect the floor's surface.

Protecting Your Floor

- **Entry Mats:** Place mats at all entrances, both inside and outside your home, where possible. This will significantly reduce the amount of dirt and abrasive particles brought onto the floor.
- **Mat Placement:** We recommend waiting at least two days after the coating is applied before placing any mats on the floor to allow the seal to fully cure.
- **Protective Pads:** Ensure all furniture that makes contact with the floor has protective pads. Regularly check these pads and replace them when they show signs of wear.