



# RECOAT ETCH

**Heavy Duty, Fast Acting Water Based Stripper Designed for Removing Crosslinked Floor Polish**



## DESCRIPTION

**Recoat Etch** is an ammoniated heavy duty, fast acting water-based stripper designed for removing crosslinked floor polishes.

## USES

**Recoat Etch** is suitable for use on concrete, linoleum, vinyl and timber floors.

## DIRECTIONS FOR USE

Do not use near (undiluted), use 300ml Recoat Etch per litre of water.

Spread freely on floor to be stripped and allow 5 minutes for the solution to act. Then machine scrub using a stiff brush or nylon stripping pad.

Mop up residue and rinse thoroughly with water and clean mop.

## LIMITATIONS

- Always read SDS before use of any product
- Do not use neat (undiluted)

## HEALTH AND SAFETY

For detailed information, refer to the current Safety Data Sheet available at [www.ecoshield.com.au](http://www.ecoshield.com.au)

For emergencies, please contact 24-hour mobile 0413 075 994.

## First Aid Instructions

If swallowed, dilute with milk or water. DO NOT induce vomiting. First aid is generally not required. Call a doctor if necessary.

If in eyes, rinse cautiously with water for several minutes. Remove contact lenses if present. Continue rinsing. May cause irritation and redness. Seek medical attention.

If on skin: wash with plenty of soap and water. May cause redness and irritation. If irritation persists, seek medical advice.

## MANUFACTURER'S COMMENT

Use with any other manufacturer's product could result in detrimental effects on the product's performance for which Ecoshield Performance Coatings holds no responsibility, and Ecoshield Performance Coatings cannot be held responsible for failure to follow application instructions.

Ecoshield Performance Coatings is continually updating materials and methods. Ensure you have the latest information.

## TYPICAL PROPERTIES

Storage Period	3 years at 5-35°C
Packaging	5 and 15L plastic containers