



# 30 PLUS

Wet Edge Extender and Flow Enhancer for Temperatures Above 30°C



## DESCRIPTION

**30 PLUS** is a specifically formulated blend for use in Polycarbonate floor coatings. It is used to enhance the flow characteristics of Polycarbonate under conditions of high temperature and/or humidity and/or dry windy atmosphere. It is also for use on large floor areas requiring maximum wet edge time.

**30 PLUS** slows evaporation and increases application working time of Carbon Coat.

**30 PLUS** is suitable for use in Ecoshield single/two pack Carbon Coat.

## USES

**30 PLUS** should be used where conditions which required the timber coating's wet edge time and application time to be extended. This is often the case in hot weather.

## DIRECTIONS FOR USE

**30 PLUS** is supplied in ready to use form. Typical recommended mix ratio is (5:100) 50ml **30 PLUS** into every 1 litre of **Carbon Coat**. This ratio will provide for noticeable effect.

Note: Curing time of our **Carbon Coat** is not significantly affected by the application of **30 PLUS**.

## HEALTH AND SAFETY

For detailed information, refer to the current Safety Data Sheet available at [www.ecoshield.com.au](http://www.ecoshield.com.au)

For emergencies, please contact 24-hour mobile 0413 075 994.

### First Aid Instructions

If swallowed, immediately give milk or water. DO NOT induce vomiting. First aid is generally not required. Call a doctor if necessary.

If in eyes, rinse cautiously with water for several minutes. Remove contact lenses if present. Continue rinsing. If irritation persists obtain medical attention.

If on skin, wash with plenty of soap and water.

## MANUFACTURER'S COMMENT

Ecoshields **30 PLUS** has been designed for use only with Ecoshield Carbon Coat timber coatings, as part of a totally integrated application system.

Use with any other manufacturer's product could result in detrimental effects on the product's performance for which

Ecoshield Performance Coatings holds no responsibility, and Ecoshield Performance Coatings cannot be held responsible for failure to follow application instructions.

Ecoshield Performance Coatings is continually updating materials and methods. Ensure you have the latest information.

## TYPICAL PROPERTIES

Appearance	Clear liquid
Odour	No odour
Specific Gravity	1.04
Flammability	Not flammable
Solubility in Water	100% Dispersible
Storage Period	2 years at 5-35°C
Packaging	1 and 5L plastic containers