



CONCRETE GRINDING LUBE

Lubricant for Diamond Tools when Grinding, Cutting or Drilling

DESCRIPTION

Concrete Grinding Lube is an innovative lubricant specifically formulated for use with diamond tooling.

Concrete Grinding Lube has proven extremely effective to significantly increase cutting speeds and substantially reduce tool wear.

USES

Concrete Grinding Lube is suitable in all diamond cutting applications, including:

- Concrete Grinding
- Concrete Cutting
- Concrete Coring
- Marble & Granite Grinding
- Marble & Granite Cutting
- Marble & Granite Polishing
- Road & Runway Grooving
- Brick & Tile Cutting

ADVANTAGES

Greater Cutting Speed

Greater cutting speed means more output per labour hour resulting in work being completed in less time. Tool costs are significantly decreased as tools maintain their cutting edges up to 35% longer.

The benefits of **Concrete Grinding Lube** increase the effectiveness of your business translating to greater profits.

Environmentally Friendly

Concrete Grinding Lube is environmentally friendly and meets Australian Standard 4351 as a readily biodegradable material.

Concrete Grinding Lube directly increases efficiency leading to further environmental benefits including reduced water and power consumption.

MIX RATIO

1 litre of **Concrete Grinding Lube** will dilute into 25 litres of water (1:25)

Concrete Grinding Lube can be used neat (undiluted) if required

LIMITATIONS

- Always read SDS before use of any product

HEALTH AND SAFETY

For detailed information, refer to the current Safety Data Sheet available at www.ecoshield.com.au

For emergencies, please contact 24-hour mobile 0413 075 994.

First Aid Instructions

Discomfort in stomach and intestinal tract may occur. Immediately give milk or water. DO NOT induce vomiting. First aid is generally not required. Call a doctor if necessary.

If in eyes, rinse cautiously with water for several minutes. Remove contact lenses if present. Continue rinsing. May cause irritation and redness. Seek medical attention if irritation persists.

If on skin: wash with plenty of soap and water. If irritation persists, seek medical advice.

MANUFACTURER'S COMMENT

Use with any other manufacturer's product could result in detrimental effects on the product's performance for which EcoShield Performance Coatings holds no responsibility, and EcoShield Performance Coatings cannot be held responsible for failure to follow application instructions.

EcoShield Performance Coatings is continually updating materials and methods. Ensure you have the latest information.

TYPICAL PROPERTIES

Appearance	Transparent reddish liquid
Specific gravity	1.04
Flashpoint	Does not burn
Storage Period	2 years at 5-35°C
Packaging	5, 15 and 200L plastic containers