



# ECO POLISH

Sacrificial High Solids Metallised Crosslinked Acrylic Sealer for Floors



## DESCRIPTION

**Eco Polish** is an extremely easy to apply, water based metallised acrylic sacrificial coating with intermediate wear resistance properties.

**Eco Polish** can be used both as a buffable and non-buffable coating that leave a high shine surface.

## USES

**Eco Polish** is designed for commercial premises where a quality surface appearance is required throughout the life of the floor.

**Eco Polish** is ideal for the temporary renewing of all hard surface flooring that is looking 'tired' or scuff worn. It will both delay the requirement for a full resurfacing and provide an 'as new' look each time it is applied.

## ADVANTAGES

- Can be applied with applicator pad or cotton mop
- Does not need buffing but can be buffed if required
- Easy to 'spot repair' scratch damage and scuff marks
- Can be applied over all coated surfaces
- Can be applied to polished concrete floors

## COVERAGE

One coat will cover approximately 30 – 40m<sup>2</sup> per litre.

## DIRECTIONS FOR USE

1. Prepare floors by removing general grime and dirt build up using **Eco Clean**.
2. When floor has dried after cleaning, apply one thin coat of **Eco Polish** and let dry.
3. Buff the floor after it is thoroughly dry with a high-speed polisher (the heat from polishing will accelerate the crosslinking of the **Eco Polish**).
4. Apply a second thin coat of **Eco Polish** and buff as before.
5. Inspect the floor for finish and if necessary, apply a third thin coat. Allow drying and buffing as previously.
6. The floor is not completely resealed and ready for use.

**Note:** **Eco Polish** can be used without buffing, however, without the heat from the buffing pad to accelerate the crosslinking cure time, air cure will take much longer.

Typically allow the **Eco Polish** to cure overnight before use of the floor (recommend 8 hours at 25°C).

## LIMITATIONS

- Always read SDS before use of any product

## HEALTH AND SAFETY

For detailed information, refer to the current Safety Data Sheet available at [www.ecoshield.com.au](http://www.ecoshield.com.au)

For emergencies, please contact 24-hour mobile 0413 075 994.

### First Aid Instructions

If swallowed, dilute with milk or water. DO NOT induce vomiting. First aid is generally not required. Call a doctor if necessary.

If in eyes, rinse cautiously with water for several minutes. Remove contact lenses if present. Continue rinsing. May cause irritation and redness. Seek medical attention.

If on skin: wash with plenty of soap and water. May cause redness and irritation. If irritation persists, seek medical advice.

## MANUFACTURER'S COMMENT

Use with any other manufacturer's product could result in detrimental effects on the product's performance for which Ecoshield Performance Coatings holds no responsibility, and Ecoshield Performance Coatings cannot be held responsible for failure to follow application instructions.

Ecoshield Performance Coatings is continually updating materials and methods. Ensure you have the latest information.

## TYPICAL PROPERTIES

Appearance	Transparent milky white liquid
Sheen	Gloss
Spread rate	30 – 40m <sup>2</sup> per litre
Dry time at 25°C	20 minutes
Storage Period	2 years at 5-35°C
Packaging	5 and 15L plastic containers