



ECO STRIP

Heavy Duty, Fast Acting Water Based Stripper Designed for Removing Crosslinked Floor Polish



DESCRIPTION

Eco Strip is an ammoniated heavy duty, fast acting water-based stripper designed for removing crosslinked floor polishes.

USES

Eco Strip is suitable for use on concrete, linoleum, vinyl and rubber floors. Do NOT use on wooden floors.

DIRECTIONS FOR USE

Concrete, Vinyl, Rubber:

Use at the rate of 300ml **Eco Strip** to 1 litre of water. Spread freely on floor to be stripped and allow 5 minutes for solution to act.

Machine scrub using a stiff brush or nylon stripping pad.

Mop up residue and rinse thoroughly with water and clean mop. Floor is now ready for sealing and re-polishing.

Linoleum:

Use 125ml **Eco Strip** to 1 litre of hot water.

LIMITATIONS

- Always read SDS before use of any product

HEALTH AND SAFETY

For detailed information, refer to the current Safety Data Sheet available at www.ecoshield.com.au

For emergencies, please contact 24-hour mobile 0413 075 994.

First Aid Instructions

If swallowed, dilute with milk or water. DO NOT induce vomiting. First aid is generally not required. Call a doctor if necessary.

If in eyes, rinse cautiously with water for several minutes. Remove contact lenses if present. Continue rinsing. May cause irritation and redness. Seek medical attention.

If on skin: wash with plenty of soap and water. May cause redness and irritation. If irritation persists, seek medical advice.

MANUFACTURER'S COMMENT

Use with any other manufacturer's product could result in detrimental effects on the product's performance for which Ecoshield Performance Coatings holds no responsibility, and Ecoshield Performance Coatings cannot be held responsible for failure to follow application instructions.

Ecoshield Performance Coatings is continually updating materials and methods. Ensure you have the latest information.

TYPICAL PROPERTIES

Appearance	Transparent liquid
Storage Period	2 years at 5-35°C
Packaging	1 and 5L plastic containers