



LIQUID GRIND

Safe to use Non-Corrosive Biodegradable Concrete Softening Agent



DESCRIPTION

Liquid Grind is a safe to use non-corrosive, biodegradable concrete softening agent that will reduce concrete density to help diamond grind hard stubborn slabs.

USES

Liquid Grind is suitable in all diamond cutting applications, including:

- Concrete grinding
- Concrete cutting
- Concrete coring

ADVANTAGES

Greater cutting speed means more output per labour hour resulting in work being completed in less time.

The benefit of **Liquid Grind** increases the effectiveness of your business, translating into greater profits.

Liquid Grind can safely be used onsite without potential environmental hazards. The product is 100% biodegradable and will not affect any stormwater runoff streams.

MIX RATIO

1 litre of **Liquid Grind** will dilute into 1 litre of water.

DIRECTIONS FOR USE

For best results use **Liquid Grind** in conditions that will prevent the surface from drying out too quickly.

Liquid Grind is best diluted in a bucket then applied directly onto the concrete floor and spread evenly with a soft bristled broom.

Liquid Grind should be applied liberally so that the concrete absorbs enough material to reach saturation.

Keep the surface wet for a minimum of 15 minutes to allow **Liquid Grind** to soften the concrete in preparation for grinding.

Always test **Liquid Grind** in a small area first.

LIMITATIONS

- Always read SDS before use of any product

HEALTH AND SAFETY

For detailed information, refer to the current Safety Data Sheet available at www.ecoshield.com.au

For emergencies, please contact 24-hour mobile 0413 075 994.

First Aid Instructions

If swallowed, dilute with milk or water. DO NOT induce vomiting. First aid is generally not required. Call a doctor if necessary.

If in eyes, rinse cautiously with water for several minutes. Remove contact lenses if present. Continue rinsing. May cause irritation and redness. Seek medical attention.

If on skin: wash with plenty of soap and water. May cause redness and irritation. If irritation persists, seek medical advice.

MANUFACTURER'S COMMENT

Use with any other manufacturer's product could result in detrimental effects on the product's performance for which Ecoshield Performance Coatings holds no responsibility, and Ecoshield Performance Coatings cannot be held responsible for failure to follow application instructions.

Ecoshield Performance Coatings is continually updating materials and methods. Ensure you have the latest information.

TYPICAL PROPERTIES

Appearance	Transparent reddish liquid
Storage Period	2 years at 5-35°C
Packaging	5, 15 and 200L plastic containers